

Model	IK65	IK75	IK86	IK98	IK110
Product picture					
Display specification					
Diagonal display size	65"	75"	86"	98"	110"
LED Brand	CSOT				
Bezel color	Aluminum frame(Black & Grey color)				
Back Light	Direct type LED				
Active area (mm)	1428.48 * 803.52	1649.66 * 927.93	1895.04 * 1065.96	2158.85 * 1214.35	2436.48 * 1370.52
Resolution	3840*2160 /UHD				
Aspect Ratio	16:9				
Contrast Ratio	1200:1/4000:1				
Colors	1.07 billion colors				
Brightness	350cd/m2				
Viewing angle	178°				
Glass hardness	Mohs-7 level				
Screen surface	4mm thickness Anti-Glare glass				
Panel Interactivity					
Touch technology	IR touch				
Touch points	20 touch points				
Touch accuracy	±2mm(Windows)				
Recognition	Finger or passive stylus				
Response Rate	<4ms(single touch) <10ms(max touch inputs)				
Minimum object size	2mm				
Response Time	<5 ms				
Windows OPS Slot	OPS & OPS-C Intel standard				
Hotspot	Yes				
Bluetooth	V 5.0				
WiFi	WIFI 6E				
System support	Win10/Win8/Win7/Mac OS /Android/Chrome OS/Linux				
Operating system					
Android Version	Android 11.0				
Chipset	Amlogic T982				
CPU	4×ARM Cortex-A55				
GPU	RM Mali-G52				
RAM	DDR4 4GB				
ROM	32GB				
Compliant with	Windows; Mac; Linux; Chrome OS				
Front side Connectivity					
Front ports	USB3.0 * 2 (Public), Touch out USB type B * 1, HDMI in 2.0 * 1, Type C* 1				
Speaker	15W*2				
Rear side Connectivity					
Rear Side ports	1. (Mini) MIC In*1 2. RS232*1 3. OPTICAL OUT*1 4. VGA *1 5. PC AUDIO IN*1 6. RJ45 in*1 6. (Mini)LINE OUT*1 7. TOUCH OUT(USB3.0)*1 8.HDMI in*2 9. USB2.0*1 10.USB3.0*1				
Physical specifications					

Net Weight/(kg±2)	43	55	80	92	110
Gross Weight/(kg±2)	53	65	93	110	144
Overall size(mm) (without bracket)	1483.8 * 884.4 * 91	1706 * 1008.5 * 91.2	1958.8 * 1148.1 * 91.2	2216 * 1301 * 101.5	2499.6 * 1474.2 * 101.5
Overall size(mm) (with bracket)/(L*H*W)	1483.8 * 884.4 * 121	1706 * 1008.5 * 121.2	1958.8 * 1148.1 * 121.2	2216 * 1314.5 * 125.5	2499.6 * 1474.2 * 137.5
Carton size(mm)/(L*H*W)	1590 * 1110 * 200	1820 * 1240 * 200	2060 * 1370 * 200	2362 * 1533 * 210	2606 * 1593.1 * 200
VESA(mm)	500*400	600*400	800*400	1000*400	1000*800
Electrical					
Input Voltage	90-264V AC				
Power Consumption(Standby)	<0.5W				
Power Consumption	Maximun< 225W	Maximun< 335W	Maximun< 450W	Maximun< 650W	Maximun< 760W
Environmental					
Working Temperature	0°C ~ 40°C				
Storage Temperature	-20°C ~ 60°C				
Working Humidity	10% ~ 90% RH				
Storage Humidity	10% ~ 60% RH				
OPS PC(Optional)					
CPU	I5(I3/I7 for optional)				
RAM	8G(4G/16G for optional)				
ROM	128G SSD (256G/512G)				
Standrad	80 PIN(Chinese Standard/international standard)				
Dimension/cm	195*180*42/119*180*30				
Camera(Optional)					
Model	UHD Camera				
Install Method	Built-in(on the middle-upper frame)				
Pixel	13MP/48MP				
FOV	Diagonal: 94°				
Compliant with OS	Windows; Android; Mac; Linux; Chrome OS				
Microphone(Optional)					
Install Method	Built-in(on the middle-upper frame)				
Number	8 Array				
Voice Pickup	0-8M				
Accessories					
Accessories	Pen * 1pcs, Remote control * 1pcs, 2m power cord * 1pcs, wall mount kit; Wireless dongle(Optional); Mobile trolley cart(Optional); Smart Pen (Optional)				